

Quick-action penetration thermometer




Checks the correct cooking temperature of sensitive food e.g. fish

The testo 106 penetration thermometer is ideal for quick, uncomplicated core temperature checks in all areas e.g. catering, hotels, industrial kitchens, supermarkets etc.

The compact, practical thermometer is "always close to hand", is pocket-sized and with its very thin and robust measuring tip it is also suitable for checks on small-sized food.

- Quick check using a thin, robust measuring tip
- Monitors limit values
- testo 106-T2 has an additional audible alarm
- Wide range with high measuring accuracy



testo 106-T1/T2 set:
Included: TopSafe, robust, waterproof, hygienic and dishwasher-safe protection case (IP 67) and wall/belt holder

testo 106-T1

testo 106-T1, penetration thermometer with probe protection cap and battery

Part no. 0560 1061



-50 to +230°C



Ordering data for Accessories

Part no.

Frozen food pre-drill Can be attached to holder clip	0554 0826
TopSafe (indestructible protection case)	0516 8265
Waterproof and dishwasher-safe protection case (IP67)	
Holder clip with probe protection cap	0554 0825
Holder clip for attachment to belt or mounting on wall; cap protects from injuries	
ISO calibration certificate/Temperature For air/immersion probes, calibration point +60°C	0520 0063
ISO calibration certificate/Temperature For air/immersion probes, calibration point -18°C	0520 0061
ISO calibration certificate/Temperature For air/immersion probes, calibration point 0°C	0520 0062
ISO calibration certificate/Temperature For air/immersion probes, calibration points -18°C; 0°C	0520 0041
ISO calibration certificate/Temperature For air/immersion probes, calibration points -8°C; 0°C; +40°C	0520 0181

Technical data

Meas. range	-50... +230 °C	Display	LCD, 1 line
Accuracy ± 1 digit	±1% of mv (+100... +230 °C) ±0.5 °C (-30... +99.9 °C) ±1 °C (-50... -30.1 °C)	Material/Housing	ABS
Resolution	0.1 °C (-50... +230 °C)	Oper. temp.	-20... +50 °C
		Storage temp.	-40... +70 °C
		Battery type	Lithium battery (2032)
		Battery life	250 h
		Dimensions	215x34x19 mm
		Weight	80 g
		Warranty	2 years

Recommended kit:

testo 106-T1 set for quick checks on operation, waterproof



testo 106-T1, penetration thermometer with probe protection cap and battery

TopSafe (indestructible protection case)

Holder clip with probe protection cap

Part no. 0563 1061

Recommended kit:

testo 106-T2 for quick checks on operation, waterproof and with alarm



testo 106-T2 set

This instrument includes the same components as the testo 106-T1 set but has an additional freely adjustable audible alarm thus making checks even more efficient.

Part no. 0563 1062